2023 CAN-AM OUTLANDER MAX 6X6 DPS 650



PACKAGE HIGHLIGHTS

- Unmatched uphill and downhill stability
- · Incredible traction and soft ground performance
- Towing and cargo carrying capability to rival most mid sized SSVs
- Selectable 4WD/6WD
- Tri-Mode Dynamic Power Steering (DPS™)
- Continuously Variable Transmission (CVT) with extra low L-gear
- Visco-Lok† QE auto-locking front differential
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Quick release rear sway bar
- 14 in. cast-aluminum wheels
- 26 in. ITP Terracross† radial tyres
- · Dump dual-level cargo box with modular accessories
- · 2 person capability, with removable passenger seat

Tundra Green / 650

ENGINE	650
Туре	62 hp, Rotax® 650 cc, V-twin, liquid-cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/extra-low L, standard engine braking
Drive Train	Selectable 4WD/6WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel
Rear Shocks	Oil
TYRES & WHEELS	
Front Tyres	ITP Terracross 26 x 8 x 14 in.
Rear Tyres	ITP Terracross 26 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

DIMENSIONS & CAPACITIES		
Estimated Dry Weight	1,100 lb (499 kg)	
LxWxH	124.8 x 48.5 x 55.3 in. (317 x 123 x 140 cm)	
Wheelbase	90 in. (228.5 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Rack Capacity	Front: 100 lb (45 kg)/Rear: 700 lb (318 kg)	
Storage Capacity	Dual-level cargo box with sidewalls and tailgate 18.5 gal (70 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
Person Capacity	2	

FEATURES

Gauge	4.5 in. digital display
Instrumentation	DC outlet, 15-A connector
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights
Winch	Prewired for available winch
Seat	Convertible Rack System (CRS)
Handlebar	Standard
Protection	Central Skid Plate

WARRANTY & EXTENDED SERVICE

WARRANT I & EXTENDED SERVICE		
Factory Warranty	2 years / 15,000 km, whichever comes first	
Service Intervals	100 hours / 12 months / 3000 km	



